Accurate and Reliable ECG Analysis Easy to Use **Motion Detector** Pace Maker Detection

Self Test Function AHA/ERC Guidelines for CPR and Defibrillation 5 Year Warranty

AUTOMATIC EXTERNAL DEFIBRILLATOR



















AUTOMATIC EXTERNAL DEFFIBRILLATOR

Life-Point Pro AED Technical Specifications

Operating Mode	Automatic
Charging Time at max Joule	typically < 10 sec
ECG Analysis Period	typically < 10 sec
Wave Form	Truncated Biphasic Wave Form
Energy Steps	Adult: 150J - 200J - 200J / Child: 50J - 50J - 50J
Pace Maker Detection	Yes
Motion Detector	Yes
Impedance Measurement	25 – 100 ohm
Maximum Discharging	typically 100 shocks (at 20 °C with full battery)
Derivation	DII
ECG Bandwidth	2 – 25 Hz
Battery Type	NiMh (14,4V / 2700 mA)
Self Test Schedule	Weekly - Monthly - Each Start
Self Test Scope	Battery - Internal Electronics - Software
Dimensions	9,5cm x 27cm x 24cm
Weight (battery included)	1850 gr
Class (93/42/EEC)	II B
Operating Conditions	0°C - 50°C ve % 10 – % 95 RH
Storage Conditions	Between -20°C and 60°C
Data Documentation	ECG Signal/ Event / Voice Record
Data Transfer	Metsis AED Software (USB/SD Kart)
Minimum Computer Requirement	Windows XP – Windows Vista – Windows 7 Pentium or higher VGA Monitor or higher CD-ROM Driver USB Port 2 Gb Free Disk Space



